

The AVB Levelling Bar with roller for NOX Tiltrotators is the ideal tool to level material for a smooth surface for excavators with up to 8t operating weight.

The PLA is the simple form without roller for excavators with up to 8t operating weight.

- ▶ **Robust design:** no protruding parts, stable construction.
- ▶ **Effective distribution and levelling** of gravel etc.
- ▶ **Different adapters** available.
- ▶ **Different widths** available.
- ▶ **Optional for AVB: scraper** for roller, so no dirt or clay remains.



here with adapter

## Levelling Bar with roller AVB

Type	for NOX	Width (mm)	Weight (kg)	Operating weight (t)
AVB 8-1800	TR06NOX / TR07NOX / TR11NOX	1800	200	< 8
AVB 8-2100	TR06NOX / TR07NOX / TR11NOX	2100	300	< 8
AVB 8-2200	TR06NOX / TR07NOX / TR11NOX	2200	420	< 8

**Package consists of:** levelling bar with roller

**Note:** adapters of other manufacturers on request

## Accessories

Type	Description
KSW03-AVB	adapter for system L-Lock KMS03L/KHS03L – up to 6,5t
KSW08-AVB	adapter for system L-Lock KMS08L/KHS08L – up to 12t
OQ40-AVB	adapter for system Oilquick OQ40 – up to 5t
OQ45-5-AVB	adapter for system Oilquick OQ45-5 – up to 12t
S40-AVB	adapter for system S-Lock KMS40S/KHS40S – up to 6t
S45-AVB	adapter for system S-Lock KMS45S/KHS45S – up to 11t
S50-AVB	adapter for system S-Lock KMS50S/KHS50S – up to 11t

## Picture



The AVB Levelling Bar with roller for NOX Tiltrotators is the ideal tool to level material for a smooth surface for excavators with up to 24t operating weight.

The PLA is the simple form without roller for excavators with up to 24t operating weight.

- ▶ **Robust design:** no protruding parts, stable construction.
- ▶ **Effective distribution and levelling** of gravel etc.
- ▶ **Different adapters** available.
- ▶ **Different widths** available.
- ▶ **Optional for AVB: scraper** for roller, so no dirt or clay remains.



here with adapter

## Levelling Bar with roller AVB

Type	for NOX	Width (mm)	Weight (kg)	Operating weight (t)
AVB 24-2500	TR14NOX / TR19NOX / TR25NOX	2500	420	< 24
AVB 24-2700	TR14NOX / TR19NOX / TR25NOX	2700	470	< 24

**Package consists of:** levelling bar with roller

**Note:** adapters of other manufacturers on request

## Accessories

Type	Description
KSW10-AVB	adapter for system L-Lock KMS10L/KHS10L – up to 19t
KSW21/25-AVB	adapter for system L-Lock KMS21/25L / KHS21/25L – up to 40t
OQ60-AVB	adapter for system Oilquick OQ60 – up to 15t
OQ60-5-AVB	adapter for system Oilquick OQ60-5 – up to 15t
OQ65-AVB	adapter for system Oilquick OQ65 – up to 22t
OQ70-AVB	adapter for system Oilquick OQ70 – up to 28t
OQ70/55-AVB	adapter for system Oilquick OQ70/55 – up to 32t
S60-AVB	adapter for system S-Lock KMS60S/KHS60S – up to 18t
S70-AVB	adapter for system S-Lock KMS70S/KHS70S – up to 30t

## Picture

