

ROAD PLANERS FOR SKID STEERS

RPL/SSL

Fixed tooth road planer for skid steers up to 135 hp.

The RPL/SSL is a road planer for skid steers from 60 to 135 hp, capable of milling up to 7 inches deep and is available in three widths of 18, 24 and 30 inches. The RPL/SSL is ideal for road preparation before adding a new layer of asphalt or concrete, or to simplify excavation

operations. Self-leveling skids and tilt ensure optimal results. Operational precision is ensured by the hydraulic drive system as well as practical depth and cutting indicators. The line is completed with teeth specifically designed for asphalt and concrete road surfaces.



60-135 hp



Depth
7 in



Cutting and depth indicators for precise operation control



Tilt for optimal results on uneven surfaces

Hydraulic side shifting for accurate positioning over the work area

Self-leveling skids With independent hydraulic position control

MAIN OPTIONS



Teeth for working on concrete



WSS Basic water injection system to reduce dust and cool the teeth



Wiring adaptors Wiring adaptors interface to allow a Plug & Play coupling with the most popular skid steers

STANDARD EQUIPMENT

Mechanical floating tilt system (tilt)	Anti-shock block valve with relief and anti-cavitation valves
Independent hydraulic skids control	Hydraulic hoses for connections
Mobile sides-frame	Interchangeable Hardox® antiwear skids plate
Hydraulic side shifting	Asphalt round bit teeth
Enclosed / anti-dust machine body	Cutting indicator
Working pressure control gauge	Diverter valve 12 V
860 cc fixed displacement hydraulic piston motor (RPL/SSL 45-60)	940 cc fixed displacement hydraulic piston motor (RPL/SSL 75)
Direct drive motor transmission	

OPTIONS

Multiple tooth options	Adaptor wiring
Water spray system WSS Basic	SAE attachment frame with integrated water tank
Roof mounted water tank kit for skid steer	

MODEL	RPL/SSL 45	RPL/SSL 60	RPL/SSL 75
Engine (hp)	60-110	60-110	90-135
Requirements Flow (gal/min)	26-41	26-41	32-45
Pressure (PSI)	2600-5080	2600-5080	2600-5080
Working width (in)	18	24	30
Total width (in)	65	65	65
Weight (lbs)	1990	2100	2200
Working depth (in)	0-7	0-7	0-7
Rotor diameter (in)	23.6	23.6	23.6
Tilting angle ±	8°	8°	8°
Side shifting (in)	22	22	22
N° picks type R	42	54	60

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE R



PICK R/44/A (standard)



PICK R/44/C (optional)